

BID SPECIFICATIONS
2009 – Chevy Silverado 3500 HD 2WD Reg Cab or Equivalent

SAFETY

- Daytime Running Lamps, with automatic exterior lamp control
- Air bags, frontal, driver and right-front passenger with passenger-side deactivation switch

MECHANICAL

- Engine, Vortec 6.0L Variable Valve timing V8 SFI (312 hp [232.6 kW] @ 4400 rpm, 373-lb-ft. [503.5 N-m] @ 4400 rpm)
- Transmission, 6-speed automatic, heavy-duty, electronically controlled with overdrive and tow/haul mode (Requires (LY6) Vortec 6.0L V8 SFI engine)
- Rear axle, 3.73 ratio
- Air cleaner, high-capacity
- Rear wheel drive
- Cooling, external engine oil cooler, heavy-duty air-to-oil, integral to driver-side of radiator tank
- Cooling, auxiliary external transmission oil cooler, heavy-duty air-to-oil
- Battery, heavy-duty 600 cold-cranking amps, maintenance-free with rundown protection and retained accessory power (Not standard with (LMM) Duramax 6.6L Turbo Diesel V8 engine)
- Alternator, 125 amps
- Recovery hooks, front, frame-mounted
- Body, Chassis Cab, includes (VF7) bumper delete
- Frame, hydroformed
- GVWR, 11,400 lbs. (5171 kg) (Standard with 2WE models only)
- Suspension, front independent, torsion bar
- Suspension, rear 3-stage springs
- Suspension Package, Handling/Trailering, heavy-duty includes 46 mm piston monotube shocks and 34mm front stabilizer bar
- Steering, power, recirculating ball
- Brakes, 4-wheel antilock, 4-wheel disc
- Exhaust, aluminized stainless-steel muffler and tailpipe

INTERIOR

- Seats, front 40/20/40 split-bench, 3-passenger, driver and front passenger manual reclining with outboard head restraints and center fold-down armrest with storage
- Seat trim, Dark Titanium vinyl (Vinyl seats require (BG9) Black rubberized vinyl floor covering)
- Air conditioning
- Floor covering, Black rubberized-vinyl
- Steering column, Tilt-Wheel, adjustable with brake/transmission shift interlock
- Steering wheel, includes theft-deterrent locking feature
- Instrumentation, analog with speedometer, fuel level, engine temperature, tachometer, voltmeter and oil pressure indicators
- Driver information Center with odometer, trip odometer and message center (monitors numerous systems including low fuel, turn signal “on”, transmission temperature and oil change notification) (Driver information Center controls are operated through the trip button unless (UK3) steering wheel mounted audio controls is ordered. On 1LT includes 8-point compass and outside temperature)
- Warning tones, headlamp on, key-in-ignition, driver and passenger buckle up reminder and turn signal on
- Cup holders, front (also includes rear cup holders on Extended Cab models)
- Mirror, inside rearview manual day/night
- Coat hooks, rear driver and passenger side

- Visors, driver and front passenger, sliding, with clip and passenger side vanity mirror with cover, Opal Gray-colored
- Assist handle, front passenger (Also includes rear assist handles in the headliner on Extended Cab Models)
- Lighting, interior with dome and reading lights, backlit instrument panel switches and door handle-activated illuminated entry
- Power outlets, 2 auxiliary instrument pane-mounted with covers, 12-volt

ENTERTAINMENT

- Audio system, AM/FM stereo with MP3 compatible CD player, seek and scan, digital clock, auto-tone control, Radio Data System (RDS), speed-compensated volume and TheftLock
- Audio system feature, 4-speaker system (Require Regular Cab models)

EXTERIOR

- Tires, LT225/75R17E all-season, blackwall (Includes 6 tires with (ZW9) pickup box delete)
- Wheels, 6 – 17" x 6.5" (4.2 cm x 16.5 cm) 8-lug painted steel, includes painted center caps
- Bumper, front chrome
- Air dam, Black
- Grille, chrome surround
- Headlamps, dual halogen composite with automatic exterior lamp control and flash-to-pass feature
- Lamps, Smoked Amber roof marker
- Mirrors, outside manual, Black, manual folding
- Glass, Solar-Ray light-tinted, all windows
- Wipers, front intermittent wet-arm with pulse washers
- Door handles, Black

BODY

- 132" Service Body; 54" Wide Floor; 84" CA; DRW
- 14 Ga. Galvanneal Construction
- 7 GA Rear Crossmember
- 1/4" Front Crossmember
- 100% E-Coat Primer inside and out
- 100% Power Coated Finish inside and out
- 132" Overall length; 80" overall width; 40" overall height
- 12 GA Floor Plate Rigidized
- Smooth Gas Spring Door Operators
- "Wiper" Style Door Seals
- Bolt-on door hinges
- Nylon Hinge Bushings
- Automotive Style Door Latches with all Stainless Steel Latch Assembly
- Slam Action Tailgate
- Removable Trays
- Stop/Turn/Tail and Backup Lights Recessed in Bumper
- Sliding Drawer Unit in One Compartment
- Reelcraft 83000 OLPJ Hose Reel Mounted in One Compartment
- MTE Standard "Pooched" Bumper with Black Powdercoat Finish
- Body Powdercoat – Red
- Electric Back-up Alarm, 97DB
- Side Mount Ladder Rack
- Heavy Duty 2" Receiver :Hitch, Mounted Below Bumper
- 7-Way Connector, Round Socket, Flat Pin, RV Style

- Utility Body – Undercoating
- Spray in Liner; Stahl 132, 11' Bodies, Loadspace Complete with Tailgate
- FS Target Tech, L.E.D. self Contained 2 Light Strobe System
- Back Rack Headache Rack with Light Bar Mounts
- Whelen Liberty Lightbar with LED Traffic Advisor
- Manual Flood Light

AUTOCRANE 5005EH

- 5000 LB. Capacity w/Power Boom Elevation
- Power Hoist and Power Rotation
- Automatic Overload Protection System for Hoist Up
- Boom extend and Boom Down Functions
- 24' Remote Control Pendant
- 2/1/2 HP 24 V Hoist Motor
- 22' Battery Cable
- 360 Deg. Rotation
- 80' of 5/16" Cable with a Breaking Strength of 9800 Lbs
- Non-tipping Swiveling Travel Block w/Latch Installed
- Boom is Power Extension from 10' to 16' and Manual Extension from 16' to 20'
- 5005EH; 10'-16'-20' Boom
- Factory Boom Rest for Utility or Platform #725043
- Crane Reinforcement for Platforms & Utility Bodies
- VMAC VR70 Underhood Air Compressor with Aux Tank on Top of Bed Under Crane Boom